



CompactPCI[®] IEEE 1394 (FireWire) Controller Comparison Chart

Document No. 2554 • Edition 2006-08

	CF2-CYMBAL Rev. 2	CF4-HIHAT	CCE-PUNK	CMF-1394
Board Form Factor	3U	3U	3U Mezzanine	PC•MIP
No. of 1394 Ports	3	3	2	1
Data Transfer Rates	100/200/400Mbps	100/200/400Mbps	100/200/400Mbps	100/200/400Mbps
Link Layer Controller (LLC) Cable Transceiver (PHY)	TI OHCI-Lynx TSB12LV26 TI TSB41AB3	TI PCILynx-2 TSB12LV21B TI TSB41AB3/TSB41LV03	TI XIO2200A Integrated PCI Express LLC/PHY	TI TSB43AA22 Integrated PCI LLC/PHY
Special Functions		Zoom Video Port	Mezzanine Companion Board for 3U CPCI CPU Carrier (e.g. CCD-CALYPSO)	Mezzanine Module for PC•MIP Carrier Boards
Compact PCI Interface	Peripheral Slot 32-Bit 33MHz	Peripheral Slot 32-Bit 33MHz		
Target Application	OHCI Compliant Software	Unibrain Legacy Software	OHCI Compliant Software	OHCI Compliant Software
Status	Active	Mature - Not For New Designs	Available 2006 Q4	Active